



Han® PushPull SCRJ POF
Assembly tools for polymer-optical fibres

Features	Technical characteristics																
<ul style="list-style-type: none"> • Cable insulation (PUR / PVC) is stripped without damage • The 'stripping' and 'precision cutting' operations are completed within the one tool • Specialized cutting method with an automatically advancing round blade for an accurate cutting result requiring no final polishing • Optical display indicating remaining operations • Simultaneous handling of twin fibers (duplex mode) 	<table border="0"> <tr> <td>Connector type</td> <td>SCRJ connector acc. to IEC 61 754-24</td> </tr> <tr> <td>Locking</td> <td>PushPull technology acc. to IEC 61 076-3-117 variant 14 (AIDA compliant)</td> </tr> <tr> <td>Insertion loss</td> <td>typically 1.5 to 2.0 dB</td> </tr> <tr> <td>Termination SC contacts</td> <td>Fast termination technique, reusable</td> </tr> <tr> <td>Fibre dimensions</td> <td>POF 980 / 1000µm</td> </tr> <tr> <td>Fibre outer diameter</td> <td>2.2 mm</td> </tr> <tr> <td>Cable outer diameter</td> <td>7 to 8.5 mm</td> </tr> <tr> <td>No. of cutting operations</td> <td>Maximum 1260</td> </tr> </table>	Connector type	SCRJ connector acc. to IEC 61 754-24	Locking	PushPull technology acc. to IEC 61 076-3-117 variant 14 (AIDA compliant)	Insertion loss	typically 1.5 to 2.0 dB	Termination SC contacts	Fast termination technique, reusable	Fibre dimensions	POF 980 / 1000µm	Fibre outer diameter	2.2 mm	Cable outer diameter	7 to 8.5 mm	No. of cutting operations	Maximum 1260
Connector type	SCRJ connector acc. to IEC 61 754-24																
Locking	PushPull technology acc. to IEC 61 076-3-117 variant 14 (AIDA compliant)																
Insertion loss	typically 1.5 to 2.0 dB																
Termination SC contacts	Fast termination technique, reusable																
Fibre dimensions	POF 980 / 1000µm																
Fibre outer diameter	2.2 mm																
Cable outer diameter	7 to 8.5 mm																
No. of cutting operations	Maximum 1260																

Identification	Part No.	Drawing
<p>Assembly tool set for POF cutting, without final polishing</p> <p>The set contains</p> <ul style="list-style-type: none"> - one stripping and cutting tool for 1260 operations - one sheath stripping tool - one Kevlar shear - one positioner for SCRJ contacts <p>Supplied in a robust plastic case</p>	<p>09 35 000 9913</p>	
<p>Replacement cutting tool for 1260 operations</p>	<p>09 35 000 9914</p>	