



Ethernet Switch
Ha-VIS eCon 4080-BPoE1
 8-port Ethernet Switch with Power over Ethernet

Unmanaged	IP 30	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
-----------	-------	---	--

Number of ports, Copper / Termination 8x 10/100Base-T(X) / M12 D-coding
 PoE supports 8 ports

Mode PoE

Input voltage / Termination 48 V DC / M12 A-coding, male
 Permissible range (min/max) 46 V ... 55 V DC
 Input current max. 3.0 A (at 48 V DC, load 350 mA per port)

Mode Non-PoE

Input voltage / Termination 24 / 48 V DC / M12 A-coding, male, for redundant power supply
 Permissible range (min/max) 12 V ... 55 V DC
 Input current approx. 150 mA (at 24 V DC)

Housing material Metal (powder coated)
 Dimensions (W x H x D) 130 x 166 x 50 mm
 Weight approx. 0.85 kg
 Operating temperature -40 °C ... +70 °C

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS eCon 4080-BPoE1
 Ethernet Switch
 with 8 ports M12 D-coding
 for wall mounting

20 77 208 3009

